

FEATURES	RT SERIES MODELS							
	RT	RTU	RTM	RTG	RTGM	RTP	RTUP	RTPM
30+ Years Life Expectancy	•	•	•	•	•	•	•	•
15-Year Warranty on Casing & Structure ¹	•	•	•	•	•	•	•	•
Nominal Tons	25 - 1,471	25 - 1,172	227 - ∞	182 - 944	178 - ∞	136 - 1,314	133 - 1,149	256 - ∞
CTI Certified Models	720	255	360	408	452	138	57	92
IBC Compliant ²	•	•	•					
Exceed energy efficiency per ASHRAE Standard 90.1	•	•	•	•	•	•	•	•
Minimum Maintenance	•	•	•	•	•	•	•	•
All-FRP Corrosion Resistant Construction	•	•	•	•	•	•	•	•
Unitized Body/Basin		•					•	
Direct Drive System	•	•	•			•	•	•
Gear Drive System				•	•			
Motor: Premium efficient, severe duty, marine duty, inverter rated, Inpro/Seal VBX bearing isolator, cast iron construction, 5-year warranty ¹	•	•	•	•	•	•	•	•
Permanent Magnet Motor ³				Optional	Optional	•	•	•
Standard Fan	•	•	•					
Low Sound Fan	•	•	•	•	•			
Super Low Sound Fan	•	•	•					
Ultra Low Sound Fan						•	•	•
Single Fan Models	•	•		•	•	•	•	
Two Fan Models	•	•	•			•	•	•
Four Fan Models	•	•				•	•	
Modular Configuration for increased capacities and to accommodate any heat load.			•		•			•

1- This Limited Warranty is valid only in the United States & Canada.

2- IBC Compliant: contact REYMSA for a list of approved models.

3- PERMANENT MAGNET MOTORS

Diference between RTP Models and RTG Models using an optional permanent magnet motor:

RTG & RTGM MODELS WITH OPTIONAL PERMANENT MAGNET MOTOR	RTP, RTUP & RTPM MODELS
Direct Drive System	Direct Drive System
Minimum maintenance	Minimum maintenance
Low Sound	Ultra Low Sound
Same capacity as standard gear drive	Increased capacity from 5 up to 15% compared to RT, RTU and RTM models.